



**Survey Kiosk K-410 AND MCD** 

Artech K-410-AND-MCD series can read and record new type of smart ID cards and open passages such as turnstiles and doors. For contactless passes, K-410 AND MCD has the ability to control access by reading QRCode or mifare type contactless cards from a mobile phone with its internal QRCode / barcode reader.

Artech Digital Signage solutions; has the advantages of cost saving and efficiency, time saving, multi-purpose usage, real time announcement publishing and prestigious corporate image.



### Features;

- ✓ Original Design
- ✓ Customization
- ✓ 3 Year Warranty and Sustainable Spare Parts Supply
- ✓ High Quality Technical Service Support
- ✓ Industrial System Technologies Experience

# Area of **Usage**





HEALTHCARE



**EDUCATION** 
























Survey Kiosk K-410 AND MCD



Interactive Design



Large Touch Screen



IP65 Front Panel Protection



Industrial Stainless Steel Body




Wide Viewing Angle, Bright and High Contrast TFT LCD Display













## **Survey Kiosk** K-410 AND MCD

#### **ORDER CODE**

Feed : 10.000mAh Lithium Ion Reader/Printer : NFC , Smart Card Reader / QR Code Reader **Operating System**: Android 6.0 CPU : 4 Cores 1.5 GHZ RAM : 2GB 1600 MHZ HDD : 16GB-eMMC



### OR CODE READER

QR CODE READER		
Scan Speed	: 300 square/sec	
Reading Format	PDF 417, GM, QR Code, DataMatrix, AZTEC, Hanxin Code, Maxicode,  Micro QR, Micro PDF417, Code One Standart	
Camera	: 1280X800 CMOS Censor	
<b>Connection Type</b>	: USB	
NFC CARD READER		
Ticket Reader	: 13.56 MHZ	
Reading Speed	: 106 Kbit/sec	
SMART CARD READER		
<b>Reading Features</b>	: ISO7816 Class A,B,C Card Reading Standart	
SYSTEM		
CPU	: 4 Cores 1.5 GHZ	
Cache	: By CPU	
Memory	: 2GB 1600MHZ	
INPUT/OUTPUT		
LAN	: 10/100/1000 Mps POE Ethernet	
Sound	: Integrated Speaker	
DATA STORAGE		
HDD/Type	: eMMC	
Storage	: 16GB-eMMC	
FEED		
UPS	: 10.000 mAh Lithium İon	
Adapter	: Adapter Included	

#### **LCD SCREEN**

Sşze/Type	: 10" LVDS 16:9
Max. Resolution	: 1280 x 800
Pixel Pitch	: 0.297mm x 0.297mm
Max. Color	: 16.7 M
Brightness	: 300cd
<b>Contrast Ratio</b>	: 1300/1
Viewing Angle	: 178°(H),178°(V)
Back Light MTBF	: 50,000 Hours
Touch Screen	: 10" Touch Capacitive
<b>ENVIRONMENTAL FEA</b>	TURES
IP Class	: Front IP65 / Back IP54
Working Temp	: -10 + 50°C
Storage Humidity	: 5 ~ 95% (Non-Condensing)
Case	: Heavy Duty Stainless Steel Case
Dimensions (WxHxD)	: Variable According to Screen Size
Mounting	: Wall - 100x100mm Wall Hang Aparatus









www.cizgi.net



